

1

Pneumatic - Spring

3/2

Ordering code

211.11.1



TYPE

32 = 3 ways



52 = 5 ways

5/2

Pneumatic - Spring



Weight gr. 3330
Minimum piloting pressure 2,5 bar



Weight gr. 4200
Minimum piloting pressure 2,5 bar

Operational characteristics

Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	6500 NI/min	mm 20	G 1"	G 1/8"

Pneumatic - Differential external

3/2

Ordering code

211.11.12



TYPE

32 = 3 ways



52 = 5 ways

5/2

Pneumatic - Differential external



Weight gr. 3330
Minimum piloting pressure 2,5 bar



Weight gr. 4200
Minimum piloting pressure 2,5 bar

Operational characteristics

Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	6500 NI/min	mm 20	G 1"	G 1/8"

Pneumatic - Pneumatic

3/2

Ordering code

211.11.11



TYPE

32 = 3 ways


52 = 5 ways

5/2

Pneumatic - Pneumatic



Weight gr. 3330
Minimum piloting pressure 2 bar



Weight gr. 4200
Minimum piloting pressure 2 bar

Operational characteristics

Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	6500 NI/min	mm 20	G 1"	G 1/8"


Pneumatic - Pneumatic

Ordering code


211.53.F.11.11

FUNCTION

- F 31 = Closed centres
32 = Open centres



Weight gr. 4200
Minimum piloting pressure 3 bar



Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	6500 NI/min	mm 20	G 1"	G 1/8"