


Flow control valve M5 - with a through bolt

Ordering code 6.01.05.F FUNCTION F 180 = Unidirectional 180/2 = Bidirectional				
Weight gr. 52				
				
 				
Operational characteristic	Fluid	Max working pressure	Operating Temperature	
	Filtered air	10 bar	Min. -5°C	Max. +70°C
				Orifice size
				mm. 2


Flow control valve G1/8" - ultrasensitive

Ordering code 6.01.18/F FUNCTION F 4 = Unidirectional 5 = Bidirectional				
Weight gr. 100				
				
 				
Operational characteristic	Fluid	Max working pressure	Operating Temperature	
	Filtered air	10 bar	Min. -5°C	Max. +70°C
				Orifice size
				mm. 3

Flow control valve G1/8" - ultrasensitive with lock nut

Ordering code 6.01.18/F FUNCTION F 6 = Unidirectional 7 = Bidirectional				
Weight gr. 105				
				
 				
Operational characteristic	Fluid	Max working pressure	Operating Temperature	
	Filtered air	10 bar	Min. -5°C	Max. +70°C
				Orifice size
				mm. 3

Flow control valve G1/8"

Ordering code 6.01.F FUNCTION F 18N = Unidirectional 18NE = Unidir. economic vers. 18/1N = Bidirectional 18/1NE = Bidir. economic vers.				
Weight gr. 50				
				
 				
Operational characteristic	Fluid	Max working pressure	Operating Temperature	
	Filtered air	10 bar	Min. -5°C	Max. +70°C
				Orifice size
				mm. 4