

1

Push button-Spring


3/2

Ordering code


T224.1.8.1

5/2



Push button-Spring



TYPE
32 = 3 ways
52 = 5 ways



Weight gr. 170
Operating force 50N



Weight gr. 200
Operating force 50N

Operational characteristics

Fluid	Max working pressure	Operating temperature	Flow rate at 6 bar with $\Delta p=1$	Ø orifice size	Working port size
Filtered air, with or without lubrication	10 bar	Min. -5°C Max. +50°C	1050 NI/min	mm 8,5	G 1/4"

Push button 2 positions


3/2

Ordering code


T224.1.8

5/2



Push button 2 positions



TYPE
32 = 3 ways
52 = 5 ways



Weight gr. 170
Operating force 13N



Weight gr. 200
Operating force 13N

Operational characteristics

Fluid	Max working pressure	Operating temperature	Flow rate at 6 bar with $\Delta p=1$	Ø orifice size	Working port size
Filtered air, with or without lubrication	10 bar	Min. -5°C Max. +50°C	1050 NI/min	mm 8,5	G 1/4"

Lever lateral-Spring


3/2

Ordering code


T224.1.9.1/C

5/2


Lever lateral-Spring



TYPE
32 = 3 ways
52 = 5 ways
LEVER COLOR
1 = Red
2 = Black
3 = Green



Weight gr. 220



Weight gr. 250

Operational characteristics

Fluid	Max working pressure	Operating temperature	Flow rate at 6 bar with $\Delta p=1$	Ø orifice size	Working port size
Filtered air, with or without lubrication	10 bar	Min. -5°C Max. +50°C	1050 NI/min	mm 8,5	G 1/4"