

1

Push button Ø22-2 positions

3/2

Ordering code

228. **T**. 6.25





TYPE

32 = 3 ways

52 = 5 ways

5/2

Push button Ø22-2 positions



Weight gr. 235
Operating force 33N

Weight gr. 235
Operating force 33N

Operational characteristics

Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size
Filtered air, with or without lubrication	10 bar	Min. -5°C Max. +70°C	540 NI/min	mm 6	G 1/8"

Switch 2 positions

3/2

Ordering code

228. **T**. 6.27





TYPE

32 = 3 ways

52 = 5 ways

5/2

Switch 2 positions



Weight gr. 230

Weight gr. 250

Operational characteristics

Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size
Filtered air, with or without lubrication	10 bar	Min. -5°C Max. +70°C	540 NI/min	mm 6	G 1/8"

Key switch 2 positions

3/2

Ordering code

228. **T**. 6.28





TYPE

32 = 3 ways

52 = 5 ways

5/2

Key switch 2 positions



Weight gr. 230

Weight gr. 250

Operational characteristics

Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size
Filtered air, with or without lubrication	10 bar	Min. -5°C Max. +70°C	540 NI/min	mm 6	G 1/8"