

1

Toggle Lever (for panel mounting) Ø 30

3/2

Ordering code

T228.1.5/C


- TYPE
T 32 = 3 ways
 52 = 5 ways
 BUTTON COLOR
C 1 = Red
 2 = Black
 3 = Green

5/2



Toggle Lever (for panel mounting) Ø 30

2 positions


2 positions



Weight gr. 168



Weight gr. 180



Operational characteristics

Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working ports size
Filtered air, with or without lubrication	10 bar	Min. -5°C Max. +50°C	620 NI/min	mm 6	G 1/8"

Toggle Lever-2 positions

3/2

Ordering code




T228.1.55/C

- TYPE
T 32 = 3 ways
 52 = 5 ways
 BUTTON COLOR
C 1 = Red
 2 = Black
 3 = Green


5/2

Toggle Lever-2 positions

Weight gr. 84



Weight gr. 96



Operational characteristics

Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working ports size
Filtered air, with or without lubrication	10 bar	Min. -5°C Max. +50°C	620 NI/min	mm 6	G 1/8"

Push button Ø 30-spring

3/2

Ordering code




T228.1.6.1/C

- TYPE
T 32 = 3 ways
 52 = 5 ways
 BUTTON COLOR
C 1 = Red
 2 = Black
 3 = Green

5/2

Push button Ø 30-spring

Weight gr. 125
Operating force 33 N



Weight gr. 137
Operating force 33 N



Operational characteristics

Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working ports size
Filtered air, with or without lubrication	10 bar	Min. -5°C Max. +50°C	620 NI/min	mm 6	G 1/8"